



Test Report: LPF-16D-48

16W Single Output Switching Power Supply

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 250 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 25 mVp-p (Max)	P
2	CONSTANT CURRENT REGION	V1= 24V~48V	I/P : 230VAC O/P : CV MODE Ta : 25°C	O/P= 24V : 0.356 A O/P= 47V : 0.357 A	P
3	OUTPUT VOLTAGE TOLERANCE	V1 : 4 %~ -4 % (Max)	I/P : 100 VAC / 305 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.188 %~ -0.167 %	P
4	LINE REGULATION	V1 : 0.5 %~ -0.5 % (Max)	I/P : 100 VAC ~ 305 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0.188 %~ -0.021 %	P
5	LOAD REGULATION	V1 : 0.5 %~ -0.5 % (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.021 %~ -0.021 %	P
6	SET UP TIME	230VAC : 500 ms (Max) 115VAC : 1500 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 292.167 ms 115VAC/ 325.372 ms	P
7	RISE TIME	230VAC : 80 ms (Max) 115VAC : 80 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 30 ms 115VAC/ 30 ms	P
8	HOLD UP TIME	230VAC : 16 ms (TYP) 115VAC : 16 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 125 ms 115VAC/ 122 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
10	DYNAMIC LOAD	V1 : 4800 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 320 mVp-p (2) 448 mVp-p	P

11

DIMMER TEST

SPEC:

*Output constant current level can be adjusted through output cable by 1 ~ 10Vdc, PWM signal or resistor between ADJ1(+) and ADJ2(-).

*Reference resistance value for output current adjustment (Typical)

Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%

*1 ~ 10V dimming function for output current adjustment (Typical)

Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%

*10V PWM signal for output current adjustment (Typical)

Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%

TEST RESULT: I/P : 230 VAC ;Ta : 25℃

1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K
	Output current	0.020A	0.055A	0.093A	0.127A	0.163A	0.198A	0.232A	0.273A	0.306A	0.339A
	%	5.88%	16.18%	27.35%	37.35%	47.94%	58.24%	68.24%	80.29%	90.00%	99.71%
2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V
	Output current	0.021A	0.057A	0.094A	0.130A	0.165A	0.201A	0.235A	0.274A	0.308A	0.341A
	%	6.18%	16.76%	27.65%	38.24%	48.53%	59.12%	69.12%	80.59%	90.59%	100.3%
3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
	Output current	0.024A	0.059A	0.095A	0.131A	0.167A	0.203A	0.238A	0.275A	0.310A	0.342A
	%	7.06%	17.35%	27.94%	38.53%	49.12%	59.71%	70.00%	80.88%	91.18%	100.6%

P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	100VAC~305 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	86 V~305V	P
			I/P : LOW-LINE-3V=97 V HIGH-LINE=305 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 305 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.95 / 230 VAC(TYP) 0.97 / 115 VAC(TYP) 0.92 / 277 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.970 / 100% PF= 0.996 / 100% PF= 0.942 / 100%	P
4	EFFICIENCY	85% (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	85.11 %	P
5	INPUT CURRENT	230V/ 0.25 A (TYP) 115V/ 0.4 A (TYP) 277V/ 0.2 A (TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	I= 0.085 A/ 230 VAC I= 0.167 A/ 115 VAC I= 0.072 A/ 277 VAC	P
6	INRUSH CURRENT	230V/ 50 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I= 36.5 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 0.75 mA / 240 VAC	I/P : 240 VAC O/P : Min LOAD Ta : 25°C	L-CASE : 0.003 mA N-CASE : 0.003 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	95 % ~ 108 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	105.35 %/ 230 VAC 104.90 %/ 115 VAC Constant Current Limiting ,recovers automatically after fault condition is removed.	P
2	OVER VOLTAGE PROTECTION	CH1 : 54 V ~ 63 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	58.16 V/ 230 VAC 58.17 V/ 115 VAC Shut down and latch off o/p voltage, re-power on to recover	P
3	OVER TEMPERATURE PROTECTION	SPEC : TSW1 : 100±5°C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 305 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed.	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	U2 Rated : IP7518: 700V / 2A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 628 V (2) 472 V (3) 612 V	P
2	Diode Peak Voltage	D101 Rated : STTH2003CT: 300V / 20A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 189 V (2) 173 V (3) 187 V	P
3	Input Capacitor Voltage	C5 Rated : 22u/450V 105°C 16*20 RH	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 426 V (2) 438 V (3) 436 V	P
4	Control IC Voltage Test	U 2 Rated : IP7518:30V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 19.2 V (2) 13.6 V (3) 19.1 V	P
5	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : NDF10N60ZG: 600V/ 10 A	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 508 V (2) 426 V (3) 442 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75 KVAC/min	I/P-O/P : 4 KVAC/min Ta : 25°C	I/P-O/P : 1.448 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ	I/P-O/P : 500 VDC Ta : 25°C /70%RH	I/P-O/P : >9999 MΩ NO DAMAGE	P
3	APPROVAL	TUV : Certificate NO : UL : File NO :			N/A

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS C	I/P:230VAC/240VAC/220VAC50HZ O/P:100%,75%,50%LOAD CLASS C ≥ 50% Ta:25°C	PASS	P
2	CONDUCTION	EN55015	I/P: 230 VAC (50HZ)/115V[60HZ] O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55015	I/P: 230 VAC (50HZ)/115V[60HZ] O/P: FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																						
1	TEMPERATURE RISE TEST	MODEL : LPF-16D-24 1. ROOM AMBIENT BURN-IN : 2.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=32.2 °C 2. HIGH AMBIENT BURN-IN : 3.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=50.1 °C <table><tr><th>NO</th><th>Position</th><th>P/N</th><th>ROOM AMBIENT Ta= 32.2 °C</th><th>HIGH AMBIENT Ta= 50.1 °C</th></tr><tr><td>1</td><td>LF2</td><td>LF-802</td><td>54.6°C</td><td>71.8°C</td></tr><tr><td>2</td><td>BD1</td><td>UD2KB80</td><td>60.7°C</td><td>77.0°C</td></tr><tr><td>3</td><td>L1</td><td>TR-6102</td><td>61.5°C</td><td>78.2°C</td></tr><tr><td>4</td><td>Q1</td><td>NDF10N60ZG</td><td>66.7°C</td><td>83.7°C</td></tr><tr><td>5</td><td>D1</td><td>MUR460</td><td>67.4°C</td><td>84.8°C</td></tr><tr><td>6</td><td>C18</td><td>47uF/50V YXM</td><td>64.6°C</td><td>81.4°C</td></tr><tr><td>7</td><td>C54</td><td>22uF/50V YXM</td><td>65.1°C</td><td>83.3°C</td></tr><tr><td>8</td><td>C5</td><td>22uF/450V RH</td><td>63.0°C</td><td>81.5°C</td></tr><tr><td>9</td><td>U1</td><td>NCP1608B</td><td>68.5°C</td><td>84.7°C</td></tr><tr><td>10</td><td>U2</td><td>IP7518</td><td>77.8°C</td><td>97.0°C</td></tr><tr><td>11</td><td>T1</td><td>TF-6360</td><td>62.8°C</td><td>80.9°C</td></tr><tr><td>12</td><td>D101</td><td>YA868C12R</td><td>54.6°C</td><td>71.3°C</td></tr><tr><td>13</td><td>C105</td><td>390u/35V ZLH</td><td>53.0°C</td><td>70.1°C</td></tr></table>			NO	Position	P/N	ROOM AMBIENT Ta= 32.2 °C	HIGH AMBIENT Ta= 50.1 °C	1	LF2	LF-802	54.6°C	71.8°C	2	BD1	UD2KB80	60.7°C	77.0°C	3	L1	TR-6102	61.5°C	78.2°C	4	Q1	NDF10N60ZG	66.7°C	83.7°C	5	D1	MUR460	67.4°C	84.8°C	6	C18	47uF/50V YXM	64.6°C	81.4°C	7	C54	22uF/50V YXM	65.1°C	83.3°C	8	C5	22uF/450V RH	63.0°C	81.5°C	9	U1	NCP1608B	68.5°C	84.7°C	10	U2	IP7518	77.8°C	97.0°C	11	T1	TF-6360	62.8°C	80.9°C	12	D101	YA868C12R	54.6°C	71.3°C	13	C105	390u/35V ZLH	53.0°C	70.1°C	P
NO	Position	P/N	ROOM AMBIENT Ta= 32.2 °C	HIGH AMBIENT Ta= 50.1 °C																																																																							
1	LF2	LF-802	54.6°C	71.8°C																																																																							
2	BD1	UD2KB80	60.7°C	77.0°C																																																																							
3	L1	TR-6102	61.5°C	78.2°C																																																																							
4	Q1	NDF10N60ZG	66.7°C	83.7°C																																																																							
5	D1	MUR460	67.4°C	84.8°C																																																																							
6	C18	47uF/50V YXM	64.6°C	81.4°C																																																																							
7	C54	22uF/50V YXM	65.1°C	83.3°C																																																																							
8	C5	22uF/450V RH	63.0°C	81.5°C																																																																							
9	U1	NCP1608B	68.5°C	84.7°C																																																																							
10	U2	IP7518	77.8°C	97.0°C																																																																							
11	T1	TF-6360	62.8°C	80.9°C																																																																							
12	D101	YA868C12R	54.6°C	71.3°C																																																																							
13	C105	390u/35V ZLH	53.0°C	70.1°C																																																																							
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 305VAC/100VAC O/P : 95 % LOAD Ta= -40°C	TEST : OK	P																																																																						
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 305 VAC O/P : 95% LOAD Ta= 50 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																						
4	TEMPERATURE COEFFICIENT	± 0.03 %(0~50°C)	I/P : 230 VAC O/P : 95% LOAD	± 0.017 %(0~50°C)	P																																																																						
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																						
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C~ +55°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec : turn off 2sec		OK	P																																																																						

7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25℃	TEST : OK	P
8	CAPACITOR LIFE CYCLE	LPF-16D-24:SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25 ℃ LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50 ℃ LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta=50 ℃ LIFE TIME	(1) 741737.5 HRS (2) 138547.5 HRS (3) 168315 HRS	P
9	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 420.1KHRS		P
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 50,000 hours @ Tcase70℃		P

SAMPLE	TEST RESULT	TESTER	APPROVAL
PRODUCT SAMPLE	PASS	ZOULF	HOWAY

2009/08/04 A50-F023