

MODEL : APV-16-5

## OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 100 mVp-p (Max)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	V1: 48 mVp-p (Max)	PASS
2	OUTPUT VOLTAGE TOLERANCE	V1: -5%~ +5% (Max)	I/P: 100VAC / 264 VAC O/P:FULL/ 0% LOAD Ta:25°C	V1: -0.64%~ 1.56 %	PASS
3	LINE REGULATION	V1: -1%~ +1% (Max)	I/P: 100 VAC ~ 264VAC O/P:FULL LOAD Ta:25°C	V1: 0%~ 0%	PASS
4	LOAD REGULATION	V1: -2%~ +2% (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: -0.455%~ 0.455 %	PASS
5	SET UP TIME	230VAC/ 1500 ms (Max) 115VAC/ 1500 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 358.274 ms 115 VAC/845.484ms	PASS
6	RISE TIME	230VAC/ 30 ms (Max) 115VAC/ 30 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/9.628 ms 115 VAC/11.080ms	PASS
7	HOLD TIME	230VAC/ 20 ms (Typ) 115VAC/ 12 ms (Typ)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 86.715ms 115 VAC/17.306ms	PASS
8	OVER/UNDERSHOOT TEST	< ±5 %	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: +3.187% -1.795%	PASS
9	DYNAMIC LOAD	V1: 1000 mVp-p	I/P: 230 VAC O/P: (1)FULL /Min LOAD 90%DUTY/1KHZ (2)FULL /Min LOAD 50%DUTY/120HZ Ta:25°C	(1) 824 mVp-p (2) 860 mVp-p	PASS

## INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90 VAC~ 264 VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	90 V~ 264 V	PASS
			(1) I/P: LOW-LINE-3V= 87 V HIGH-LINE+15%= 300 V O/P: FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (2) I/P: 230VAC ON: 0.5 Sec . OFF: 0.5 Sec 20MIN (AC POWER ON/OFF NO DAMAGE )	TEST: (1) OK (2) OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P: 90 VAC ~264 VAC O/P: FULL~MIN LOAD Ta: 25°C	TEST: OK	PASS
3	EFFICIENCY	76 % (Typ)	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	76.63%	PASS
4	INPUT CURRENT	230 V/ 0.3 A (Typ) 115 V/ 0.5 A (Typ)	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	I = 0.175A / 230VAC I = 0.269A / 115VAC	PASS
5	INRUSH CURRENT	230 V/ 70 A 115 V/ 35 A COLD START	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	I = 32.484 A / 230VAC I = 14.296 A / 115VAC	PASS

## PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105% RATED OUTPUT POWER	I/P: 264 VAC I/P: 230 VAC I/P: 100 VAC O/P: TESTING Ta: 25°C	126 %/264VAC 131 %/ 230VAC 126 %/ 100 VAC  Hiccup Mode	PASS
2	OVER VOLTAGE PROTECTION	CH1: 5.75 V~ 6.75 V	I/P: 264 VAC I/P: 230 VAC I/P: 90 VAC O/P: MIN LOAD Ta: 25°C	6.03 V/ 264VAC 6.03 V/ 230VAC 6.03 V/ 90VAC Shut off O/P voltage, clamping by zener diode	PASS
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE  Hiccup Mode	PASS

## ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT																																																																						
1	TEMPERATURE RISE TEST	MODEL : APV-16-5 1. ROOM AMBIENT BURN-IN : 2 HRS I/P: 230 VAC O/P: 100% LOAD Ta= 29.5 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P: 230 VAC O/P: 100% LOAD Ta= 46.8 °C			PASS																																																																						
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 29.5 °C</th> <th>HIGH AMBIENT Ta= 46.8 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>BD1</td><td>KBP208G</td><td>56.7°C</td><td>74.0°C</td></tr> <tr><td>2</td><td>C5</td><td>15uF/400V KM</td><td>54.2°C</td><td>71.9°C</td></tr> <tr><td>3</td><td>C6</td><td>15uF/400V KM</td><td>65.0°C</td><td>82.2°C</td></tr> <tr><td>4</td><td>L1</td><td>DRGZ001D</td><td>59.7°C</td><td>77.4°C</td></tr> <tr><td>5</td><td>D1</td><td>1N4007</td><td>74.3°C</td><td>91.6°C</td></tr> <tr><td>6</td><td>T1</td><td>TF-6327</td><td>85.2°C</td><td>101.6°C</td></tr> <tr><td>7</td><td>U1</td><td>SD4843</td><td>71.0°C</td><td>87.9°C</td></tr> <tr><td>8</td><td>C9</td><td>22uF/50V KY</td><td>64.5°C</td><td>81.4°C</td></tr> <tr><td>9</td><td>D10</td><td>SB540</td><td>90.6°C</td><td>107.0°C</td></tr> <tr><td>10</td><td>C15</td><td>470u/16V ZLJ</td><td>87.0°C</td><td>102.7°C</td></tr> <tr><td>11</td><td>C17</td><td>470uF/16V ZLH</td><td>82.8°C</td><td>98.5°C</td></tr> <tr><td>12</td><td>L10</td><td>DR007D</td><td>76.9°C</td><td>93.9°C</td></tr> <tr><td>13</td><td>R12</td><td>2W 0.062Ω</td><td>82.6°C</td><td>98.6°C</td></tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 29.5 °C	HIGH AMBIENT Ta= 46.8 °C	1	BD1	KBP208G	56.7°C	74.0°C	2	C5	15uF/400V KM	54.2°C	71.9°C	3	C6	15uF/400V KM	65.0°C	82.2°C	4	L1	DRGZ001D	59.7°C	77.4°C	5	D1	1N4007	74.3°C	91.6°C	6	T1	TF-6327	85.2°C	101.6°C	7	U1	SD4843	71.0°C	87.9°C	8	C9	22uF/50V KY	64.5°C	81.4°C	9	D10	SB540	90.6°C	107.0°C	10	C15	470u/16V ZLJ	87.0°C	102.7°C	11	C17	470uF/16V ZLH	82.8°C	98.5°C	12	L10	DR007D	76.9°C	93.9°C	13	R12	2W 0.062Ω	82.6°C	98.6°C		
NO	Position	P/N	ROOM AMBIENT Ta= 29.5 °C	HIGH AMBIENT Ta= 46.8 °C																																																																							
1	BD1	KBP208G	56.7°C	74.0°C																																																																							
2	C5	15uF/400V KM	54.2°C	71.9°C																																																																							
3	C6	15uF/400V KM	65.0°C	82.2°C																																																																							
4	L1	DRGZ001D	59.7°C	77.4°C																																																																							
5	D1	1N4007	74.3°C	91.6°C																																																																							
6	T1	TF-6327	85.2°C	101.6°C																																																																							
7	U1	SD4843	71.0°C	87.9°C																																																																							
8	C9	22uF/50V KY	64.5°C	81.4°C																																																																							
9	D10	SB540	90.6°C	107.0°C																																																																							
10	C15	470u/16V ZLJ	87.0°C	102.7°C																																																																							
11	C17	470uF/16V ZLH	82.8°C	98.5°C																																																																							
12	L10	DR007D	76.9°C	93.9°C																																																																							
13	R12	2W 0.062Ω	82.6°C	98.6°C																																																																							
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR ( MIN )	I/P: 230 VAC O/P: 140% LOAD Ta:25°C	TEST : OK	PASS																																																																						
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 264 VAC/100 VAC O/P: 100% LOAD Ta= -30 °C	TEST : OK	PASS																																																																						
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 40 °C NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 40 °C HUMIDITY= 95 %R.H	TEST : OK	PASS																																																																						
5	TEMPERATURE COEFFICIENT	± 0.03 %(0~50°C)	I/P: 230 VAC O/P:FULL LOAD	± 0.018 %(0~50°C)	PASS																																																																						
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~+85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		TEST : OK	PASS																																																																						
7.	THERMAL SHOCK TEST	1. Thermal shock Temperature : -35 °C~+45 °C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load 58SEC ON/2SEC OFF		TEST : OK	PASS																																																																						
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	PASS																																																																						

9	CAPACITOR LIFE CYCLE	APV-16-5: SUPPOSE C15 IS THE MOST CRITICAL COMPONENT (1) I/P: 230 VAC O/P:FULL LOAD Ta= 25 °C LIFE TIME= 46781 HRS (2) I/P: 230 VAC O/P:FULL LOAD Ta= 40 °C LIFE TIME= 18476 HRS (3) I/P: 230 VAC O/P:75% LOAD Ta= 40 °C LIFE TIME= 43046 HRS (4) I/P: 230 VAC O/P:50% LOAD Ta= 40 °C LIFE TIME= 115872 HRS	PASS
10	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1145.7K HRS	PASS
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 20,000 hours @ Tcase 60°C , 50,000 hours @ Tcase 45°C for 5v 20,000 hours @ Tcase 70°C , 50,000 hours @ Tcase 55°C or 12v~24v	PASS

## SAFETY TEST

1	WITHSTAND VOLTAGE	I/P-O/P: 3.75 KVAC/min EN 60950	I/P-O/P: 4.2 KVAC/min Ta:25°C	I/P-O/P: 1.495 mA NO DAMAGE	PASS
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C	I/P-O/P: >9999 MΩ NO DAMAGE	PASS
3	LEAKAGE CURRENT	< 0.25 mA / 240VAC EN 60950	I/P: 264 VAC O/P:NO LOAD Ta:25°C	L-FG: 2.3 uA N-FG: 2.3 uA	PASS

## E.M.C TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 220V/230V/240V AC 50HZ O/P:100%/75%/50%/25% LOAD Ta:25°C	PASS	PASS
2	CONDUCTION	EN55015	I/P:230 VAC (50HZ) /115V(60HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	PASS
3	RADIATION	EN55015	I/P: 230 VAC (50HZ)/115V(60HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	PASS
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	PASS
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	PASS
6	SURGE	EN61000-4-5 LIGHT INDUSTRY L-N :2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	PASS
7	Test by certified Lab & Test Report Prepare				

## COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	U1 Rated SD4843 : 650 V 11 A	I/P:High-Line +3V =267 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz  I/P:Low-Line -3V = 87 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz  Ta:25°C	(1)576V (2)576V (3)562V (4)508V  (1)329V (2)302V (3)317V (4)271V	PASS
2	Diode Peak Voltage	D10 Rated SB540 : 40 V 5 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz  I/P:Low-Line -3V = 87 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz  Ta:25°C	(1)39.4V (2)35.0V (3)35.2V (4)34.6V  (1)17.4V (2)11.5V (3)15.8 V (4)16.2V	PASS
3	Clamp Diode Peak Voltage	D 1 Rated 1N4007 : 1000 V 1 A	I/P:High-Line +3V = 267 V O/P: (1)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (2)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz  Ta:25°C	(1) 536 V (2) 488 V	PASS
4	Input Capacitor Voltage	C 6 Rated CAPXON : 15 u/ 400 V 105°C/ KM Series	I/P:High-Line +3V =267 V O/P: (1)Full Load input on/off (2)Min load input on /Off (3)Burn-IN 1Hour  Ta:25°C	(1) 394 V (2) 386 V (3) 340 V	PASS
5	Control IC Voltage Test	U 1 Rated SD4843 : 21 V	I/P:High-Line +3V = 267 V O/P:(1).FULL LOAD (2).Output Short (3).O.L.P (4).O.V.P. (5).NO LOAD LOW LINE  Ta:25°C	(1)12.8V (2)12.3V (3)12.7V (4)12.3V (5)10.0V	PASS



2007/11/26 A50-G058

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2011/3/3	RD SAMPLE	PASS	SKY	HOWAY
2011/6/10	PRODUCT SAMPLE (W1106A201)	PASS	SKY	HOWAY
2011/7/30	PRODUCT SAMPLE (W1107G181)	PASS	SKY	HOWAY