



Material	INOX 1.4404 / INOX 1.4305
Klemmeinsatz	PVDF
Formdichtung	FKM
Material O-Ring	FKM
Schutzart	IP 68 – 10 bar / IP 69 K
NEMA Type Rating	4 / 4X / 6
Temperaturbereich	-35°C bis +150°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Art.-Nr. INOX 1.4404	Art.-Nr. INOX 1.4305
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.676.1200.51	1.696.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.676.1200.50	1.696.1200.50
M16 x 1,5	3 – 7	6	22	22/22	5	1.676.1600.51	1.696.1600.51
M16 x 1,5	5 – 10	6	22	22/22	5	1.676.1600.50	1.696.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.676.2000.51	1.696.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.676.2000.50	1.696.2000.50
M25 x 1,5	9 – 16	7	24	30/30	12	1.676.2500.51	1.696.2500.51
M25 x 1,5	13 – 18	7	24	30/30	12	1.676.2500.50	1.696.2500.50
M32 x 1,5	13 – 20	8	31	41/41	15	1.676.3200.51	1.696.3200.51
M32 x 1,5	18 – 25	8	31	41/41	15	1.676.3200.50	1.696.3200.50
M40 x 1,5	20 – 26	8	37	50/50	15	1.676.4000.51	1.696.4000.51
M40 x 1,5	22 – 32	8	37	50/50	15	1.676.4000.50	1.696.4000.50

