



Material	Elastomer
Ex-Schutzstufe	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperaturbereich	-40°C bis +95°C
Farbe	schwarz
RAL	9005

RoHS

passend zu AG	passend zu AG2	passend zu AG3	D mm	d mm	H mm	h mm	Art.-Nr.
PG 7	M12 x 1,5		8,5	6,3	11,5	4,5	1.296.0701.11
PG 9	M16 x 1,5	NPT 3/8"	11	7,8	13,5	5,5	1.296.0901.11
PG 11	M16 x 1,5		13,5	9,8	14,5	5,5	1.296.1101.11
PG 13,5	M20 x 1,5	NPT 1/2"	16	11,8	18	8	1.296.1301.11
PG 16	M20 x 1,5	NPT 1/2" / 16	18,5	13,8	19	9	1.296.1601.11
PG 21	M25 x 1,5	NPT 3/4"	22	17,8	22	11	1.296.2101.11
PG 29	M32 x 1,5	NPT 1" / NPT 1 1/4"	29	25	25	10	1.296.2901.11
PG 36	M40 x 1,5	NPT 1 1/2"	38	32	28	11	1.296.3601.11
PG 42	M50 x 1,5		43	38	30	12	1.296.4201.11
PG 48	M63 x 1,5		49	44	30	12	1.296.4801.11



zur Montageanleitung

