


Kunststoffkabelverschraubungen

HSK-W-Flex (metrisch, PG, NPT)



Material	Polyamid
Formdichtung	NBR
Material O-Ring	NBR
Schutzart	IP 68
Temperaturbereich	-40°C bis +100°C
Farbe	grau / schwarz
RAL	7035 / 9005

RoHS

// andere Dichtungsmaterialien z.B. Silikon auf Anfrage

AG	∅k mm	d mm	GL mm	H mm	L mm	SW mm	⊕ Nm	Art.-Nr. grau	Art.-Nr. schwarz
M16 x 1,5	2-6	8,5	8	23	85	19	2,5	1.314.1600.51	1.314.1601.51
M16 x 1,5	4-8	8,5	8	23	85	19	2,5	1.314.1600.50	1.314.1601.50
M20 x 1,5	5-9	13	9	30,5	119	24	4	1.314.2000.51	1.314.2001.51
M20 x 1,5	6-12	13	9	30,5	119	24	4	1.314.2000.50	1.314.2001.50
M25 x 1,5	9-16	20	11	40	156	33	6	1.314.2500.51	1.314.2501.51
M25 x 1,5	13-18	20	11	40	156	33	6	1.314.2500.50	1.314.2501.50
PG 9	2-6	8,5	8	23	85	19	2,5	1.314.0900.15	1.314.0901.15
PG 9	4-8	8,5	8	23	85	19	2,5	1.314.0900.14	1.314.0901.14
PG 11	3-7	10,5	8	27	103	22	2,5	1.314.1100.15	1.314.1101.15
PG 11	5-10	10,5	8	27	103	22	4	1.314.1100.14	1.314.1101.14
PG 13,5	5-9	13	9	30,5	119	24	4	1.314.1300.15	1.314.1301.15
PG 13,5	6-12	13	9	30,5	119	24	4	1.314.1300.14	1.314.1301.14
PG 16	7-12	15,5	10	32,5	130	27	4	1.314.1600.15	1.314.1601.15
PG 16	10-14	15,5	10	32,5	130	27	6	1.314.1600.14	1.314.1601.14
PG 21	9-16	20	11	40	156	33	6	1.314.2100.15	1.314.2101.15
PG 21	13-18	20	11	40	156	33	6	1.314.2100.14	1.314.2101.14
NPT 3/8"	2-6	8,5	15	23	85	19	2,5	1.314.3800.71	1.314.3801.71
NPT 3/8"	4-8	8,5	15	23	85	19	2,5	1.314.3800.70	1.314.3801.70
NPT 1/2"	5-9	13	13	30,5	119	24	4	1.314.1200.71	1.314.1201.71
NPT 1/2"	6-12	13	13	30,5	119	24	4	1.314.1200.70	1.314.1201.70
NPT 1/2"	7-12	15,5	13	31,5	130	27	4	1.314.1216.71	1.314.1217.71
NPT 1/2"	10-14	15,5	13	31,5	130	27	6	1.314.1216.70	1.314.1217.70
NPT 3/4"	9-16	20	13	40	156	33	6	1.314.3400.71	1.314.3401.71
NPT 3/4"	13-18	20	13	40	156	33	6	1.314.3400.70	1.314.3401.70

