


Reduzierung RSD-INOX (metrisch, PG)



Material	INOX 1.4305
Material O-Ring	NBR
Schutzart	IP 68 – 10 bar / IP 69 K
Temperaturbereich	-20°C bis +95°C

RoHS

// andere O-Ring-Materialien auf Anfrage

AG	IG	GL mm	H mm	SW mm	Art.-Nr.
M16 x 1,5	M12 x 1,5	6	9	19	1.097.1612.50
M20 x 1,5	M12 x 1,5	6	9,5	22	1.097.2012.50
M20 x 1,5	M16 x 1,5	6	9,5	22	1.097.2016.50
M25 x 1,5	M16 x 1,5	7	10,5	30	1.097.2516.50
M25 x 1,5	M20 x 1,5	7	10,5	30	1.097.2520.50
M32 x 1,5	M16 x 1,5	8	12,5	41	1.097.3216.50
M32 x 1,5	M20 x 1,5	8	12,5	41	1.097.3220.50
M32 x 1,5	M25 x 1,5	8	12,5	41	1.097.3225.50
M40 x 1,5	M20 x 1,5	8	13	46	1.097.4020.50
M40 x 1,5	M25 x 1,5	8	13	46	1.097.4025.50
M40 x 1,5	M32 x 1,5	8	13	46	1.097.4032.50
M50 x 1,5	M25 x 1,5	9	15	55	1.097.5025.50
M50 x 1,5	M32 x 1,5	9	15	55	1.097.5032.50
M50 x 1,5	M40 x 1,5	9	15	55	1.097.5040.50
M63 x 1,5	M32 x 1,5	10	16,5	65	1.097.6332.50
M63 x 1,5	M40 x 1,5	10	16,5	65	1.097.6340.50
M63 x 1,5	M50 x 1,5	10	16,5	65	1.097.6350.50
PG 9	PG 7	6	8,8	17	1.097.0907.01
PG 11	PG 7	6	9	22	1.097.1107.01
PG 11	PG 9	6	9	22	1.097.1109.01
PG 13,5	PG 9	6,5	9,5	22	1.097.1309.01
PG 13,5	PG 11	6,5	9,5	22	1.097.1311.01
PG 16	PG 9	6,5	9,5	24	1.097.1609.01
PG 16	PG 11	6,5	9,5	24	1.097.1611.01
PG 16	PG 13,5	6,5	9,5	24	1.097.1613.01
PG 21	PG 11	7	10,3	30	1.097.2111.01
PG 21	PG 13,5	7	10,3	30	1.097.2113.01
PG 21	PG 16	7	10,3	30	1.097.2116.01
PG 29	PG 16	8	11,5	41	1.097.2916.01
PG 29	PG 21	8	11,5	41	1.097.2921.01
PG 36	PG 21	9	12,5	50	1.097.3621.01
PG 36	PG 29	9	12,5	50	1.097.3629.01
PG 42	PG 29	10	13,5	60	1.097.4229.01
PG 42	PG 36	10	13,5	60	1.097.4236.01
PG 48	PG 36	10	13,5	65	1.097.4836.01
PG 48	PG 42	10	13,5	65	1.097.4842.01