

# Technical Data Sheet

## ECS Contact Cleaner

Art. Nr. 702

### Product description

CONTACT CLEANER is based on a special balanced mixture of high-quality, powerful and clean solvents. The low surface tension and wetting ability guaranties a quick penetration of the surface pores, removing oil, grease, dirt and other contaminants. CONTACT CLEANER evaporates quickly and leaves no residues. It is of functional use wherever high quality cleaning is required.

### Application

CONTACT CLEANER can be used anywhere where a gentle but effective cleaning of electronic components is desired, e.g. with electromagnetic contacts, relays, sensors, distributors, but also manufacture printed circuit boards. Also particularly suitable for use with sensitive precision instruments. CONTACT CLEANER can also be used as a supplement or as a substitute for ultrasonic cleaning. Aerosol can is equipped with 360° valve and can be sprayed overhead.

### Please note

CONTACT CLEANER provides a rapid and reliable cleaning. The clean areas to be cleaned with strong bursts. Fit for hard to reach places spray lance and clean means of targeted spray. Do not use near flame or hot backrests off power supplied equipment before use. Allow to dry completely solvent before switching.

Note cleaning instructions of the device manufacturer!

Electronical devices to be switched-off during cleaning and plug to be taken out. Cleaning instructions of appliance producer to be taken into account. Further information concerning CONTACT CLEANER to be found in recent MSDS.



### Technical Data

Appearance:	Clear, colorless liquid
Odor:	Alcohol
Evaporation:	Rapid
Residue:	None
Density at 20°C:	0,67g/cm <sup>3</sup>
Flash point:	2,43 mPas < 0°C
Material compatibility:	Good
Surface tension:	22mN/m

### Storage/ Shelf Life

Shelf life is 5 years if stored correctly.

