


EXIOS-Kabelverschraubungen für „Hazardous Areas“

EXIOS A2F Messing vernickelt (metrisch, NPT)



Material	Messing vernickelt
Klemmeinsatz	Polyamid 6
Formdichtung	VMQ (Silikon)
Material O-Ring	VMQ (Silikon)
Schutzart	IP 66 / IP 67 / IP 68 – 5 bar
Ex-Schutzstufe	II 2G Ex db eb IIC Gb / II 1D Ex ta IIC Da / Class I Div 2 Groups A,B,C,D / Class II Div 1 Groups E,F,G
Temperaturbereich	-60°C bis +105°C

RoHS

AG	Größe	D mm	A1 mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Art.-Nr.
M16 x 1,5	20-1	27	6 – 12	16	35,6	22/22	8	1.608.1603.50
M20 x 1,5	20-1	27	6 – 12	16	35,6	22/22	8	1.608.2003.50
M20 x 1,5	20-2	29	9 – 16	16	39,7	24/24	8	1.608.2003.51
M25 x 1,5	20-3	35	12,5 – 20,5	16	47,5	30/30	12	1.608.2503.50
M32 x 1,5	25	42	16,9 – 26	16	47,8	36/36	18	1.608.3203.50
M40 x 1,5	32	52	22 – 33	16	51,1	46/46	30	1.608.4003.50
M50 x 1,5	40	64	28 – 41	16	56,8	55/55	50	1.608.5003.50
M63 x 1,5	50	73	40 – 52,6	16	65,4	65/65	60	1.608.6303.50
M75 x 1,5	63	90	51 – 65,3	16	70,3	80/80	65	1.608.7503.50
M90 x 2,0	75	107	62 – 78	20	76,2	95/95	135	1.608.9003.50
NPT 3/8"	20-1	27	6 – 12	16	35,6	22/22	8	1.608.3803.70
NPT 1/2"	20-1	29	6 – 12	20	39,7	24/24	8	1.608.1203.70
NPT 1/2"	20-2	27	9 – 16	20	35,6	22/24	8	1.608.1203.71
NPT 3/4"	20-3	35	12,5 – 20,5	20,5	47,5	30/30	12	1.608.3403.70
NPT 1"	25	42	16,9 – 26	25	47,8	36/36	18	1.608.1003.70
NPT 1 1/4"	32	52	22 – 33	26	51,1	46/46	30	1.608.5403.70
NPT 1 1/2"	40	64	28 – 41	26,5	56,8	55/55	50	1.608.6403.70
NPT 2"	50	73	40 – 52,6	27	65,4	65/65	60	1.608.2003.70
NPT 2 1/2"	63	90	51 – 61	40	70,3	80/80	65	1.608.5203.70
NPT 3"	75	107	62 – 78	41,5	76,2	95/95	135	1.608.3003.70



zum Produktvideo



zur Montageanleitung

