



Material	Polyamid, glasfaserverstärkt
Formdichtung	NBR
Material O-Ring	NBR
Schutzart	IP 68 – 10 bar
Ex-Schutzstufe	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da / Class I Div 2 Groups A,B,C,D / Class II Div 1 Groups E,F,G
Temperaturbereich	-20°C bis +85°C
Farbe	schwarz / blau-schwarz
RAL	9005 / 5012

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	⊕ Nm	Art.-Nr. schwarz	Art.-Nr. blau-schwarz
NPT 3/8"	3 – 6	15	22	19/22	2	1.292.3801.71	1.292.3802.71
NPT 3/8"	4 – 8	15	22	19/22	2	1.292.3801.70	1.292.3802.70
NPT 1/2"	5 – 9	13	27	24/24	4,5	1.292.1201.71	1.292.1202.71
NPT 1/2"	6 – 12	13	27	24/24	4,5	1.292.1201.70	1.292.1202.70
NPT 1/2"	7 – 12	13	28	27/27	4,5	1.292.1216.71	1.292.1217.71
NPT 1/2"	10 – 14	13	28	27/27	4,5	1.292.1216.70	1.292.1217.70
NPT 3/4"	9 – 16	14	31	33/33	5	1.292.3401.71	1.292.3402.71
NPT 3/4"	13 – 18	14	31	33/33	5	1.292.3401.70	1.292.3402.70
NPT 1"	13 – 20	19	39	42/42	6,5	1.292.1001.71	1.292.1002.71
NPT 1"	18 – 25	19	39	42/42	6,5	1.292.1001.70	1.292.1002.70
NPT 1 1/4"	13 – 20	16	39	42/46	6,5	1.292.5401.71	1.292.5402.71
NPT 1 1/4"	18 – 25	16	39	42/46	6,5	1.292.5401.70	1.292.5402.70
NPT 1 1/2"	20 – 26	20	48	53/53	10	1.292.6401.71	1.292.6402.71
NPT 1 1/2"	22 – 32	20	48	53/53	10	1.292.6401.70	1.292.6402.70



zur Montageanleitung

