



Material	INOX 1.4404
Formdichtung	VMQ (Silikon)
Schutzart	IP 69 K / IP 68 – 10 bar / IP 66
Temperaturbereich	-40°C bis +120°C

**EMV  
EMC**

- // EMV Anschlussmöglichkeit integriert
- // VDMA Riboflavintest bestanden
- // EHEDG 01 Reinigbarkeitstest bestanden
- // EHEDG Certificate EL class I AUX zugelassen

AG	∅∅ mm	D mm	GL mm	H mm	SW1/SW2 mm	⊕ Nm	Art.-Nr.
M12 x 1,5	5 – 6,5	21	6	19	14/14	8	1.740.1203.50
M16 x 1,5	6 – 7,5	27	6	20	19/21	15	1.740.1603.51
M16 x 1,5	7,5 – 10	27	6	20	19/21	15	1.740.1603.50
M20 x 1,5	9 – 12	33	6	22,5	24/27	30	1.740.2003.51
M20 x 1,5	11 – 13,5	33	6	22,5	24/27	30	1.740.2003.50
M25 x 1,5	14 – 16	38	7	23,5	30/30	35	1.740.2503.52
M25 x 1,5	15 – 18	38	7	23,5	30/30	35	1.740.2503.50
M32 x 1,5	18 – 21	45	8	26,5	36/36	40	1.740.3203.51
M32 x 1,5	21 – 25	45	8	26,5	36/36	40	1.740.3203.50



zur Montageanleitung

