


Material	Messing vernickelt
Klemmeinsatz	Polyamid VO nach UL94
Formdichtung	FKM
Material O-Ring	FKM
Schutzart	IP 68 – 10 bar / IP 69 K
Ex-Schutzstufe	II 1D Ex ta IIIC Da / II 2G Ex db IIC Gb
Temperaturbereich	-60°C bis +105°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Art.-Nr.
M12 x 1,5	2 – 5	16	18,7	14/14	7,5	1.622.1200.51
M12 x 1,5	3 – 6,5	16	18,7	14/14	7,5	1.622.1200.50
M16 x 1,5	3 – 7	16	22	20/20	9	1.622.1600.51
M16 x 1,5	5 – 10	16	22	20/20	9	1.622.1600.50
M20 x 1,5	7 – 12	16	25	24/24	10	1.622.2000.51
M20 x 1,5	10 – 14	16	25	24/24	10	1.622.2000.50
M25 x 1,5	9 – 16	16	26,5	30/30	12	1.622.2500.51
M25 x 1,5	13 – 18	16	26,5	30/30	12	1.622.2500.50
M32 x 1,5	14 – 20	16	32	40/40	15	1.622.3200.51
M32 x 1,5	18 – 25	16	32	40/40	15	1.622.3200.50
M40 x 1,5	20 – 26	16	38,5	50/50	24	1.622.4000.51
M40 x 1,5	22 – 32	16	38,5	50/50	24	1.622.4000.50



zur Montageanleitung

