


# Metallkabelverschraubungen

**HSK-XL** (metrisch, G)



Material	Messing vernickelt
Formdichtung	NBR
Material O-Ring	NBR
Schutzart	IP 68
Temperaturbereich	-20°C bis +100°C

RoHS

// INOX auf Anfrage

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Nm	Art.-Nr.
M63 x 1,5	48 – 55	10	42	75/75	40	1.106.6375.50
M75 x 1,5	48 – 55	15	42	80/80	40	1.106.7500.50
M75 x 1,5	53 – 60	15	42	85/85	60	1.106.7500.51
M80 x 2	58 – 65	15	42	90/90	70	1.106.8000.50
M90 x 2	63 – 70	15	42	100/100	140	1.106.9000.50
M90 x 2	68 – 75	15	52	100/100	140	1.106.9000.51
M100 x 2	73 – 80	20	52	110/110	140	1.106.1000.51
M100 x 2	78 – 85	20	52	110/110	140	1.106.1000.50
M110 x 2	83 – 90	20	52	120/120	160	1.106.1100.51
G 2 1/2"	48 – 55	18	42	80/80	40	1.106.5200.01
G 2 1/2"	53 – 60	18	42	85/85	60	1.106.5201.01
G 3"	58 – 65	18	42	90/90	70	1.106.3000.01
G 3"	63 – 70	18	42	100/100	140	1.106.3001.01
G 4"	68 – 75	22	52	100/120	140	1.106.4000.01
G 4"	73 – 80	22	52	110/120	140	1.106.4001.01
G 4"	78 – 85	22	52	110/120	140	1.106.4002.01
G 4"	83 – 90	22	52	120/120	160	1.106.4003.01

