


Verschluss V-INOX-Ex (metrisch, PG)



Material	INOX 1.4305
Material O-Ring	NBR
Schutzart	IP 68 – 10 bar / IP 69 K
Ex-Schutzstufe	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperaturbereich	-20°C bis +95°C

RoHS

AG	GL mm	H mm	SW mm	Art.-Nr.
M12 x 1,5	6,5	9,5	14	1.192.1200.50
M16 x 1,5	6	9	19	1.192.1600.50
M20 x 1,5	6	9,5	22	1.192.2000.50
M25 x 1,5	7	10,5	30	1.192.2500.50
M32 x 1,5	8	12,5	41	1.192.3200.50
M40 x 1,5	8	13	46	1.192.4000.50
M50 x 1,5	9	15	55	1.192.5000.50
M63 x 1,5	10	16,5	70	1.192.6300.50
PG 7	5	8	14	1.192.0700.01
PG 9	6	9	17	1.192.0900.01
PG 11	6	9,5	20	1.192.1100.01
PG 13,5	6,5	10	22	1.192.1300.01
PG 16	6,5	10	24	1.192.1600.01
PG 21	7	10,5	30	1.192.2100.01
PG 29	8	12,5	41	1.192.2900.01
PG 36	8	13	50	1.192.3600.01
PG 42	9	15	58	1.192.4200.01
PG 48	10	16,5	65	1.192.4800.01



zur Montageanleitung

