


Verschluss V-INOX (metrisch, PG)



Material	INOX 1.4305
Material O-Ring	NBR / FKM / VMQ (Silikon)
Schutzart	IP 68 – 10 bar / IP 69 K
Temperaturbereich	-20°C bis +95°C / -20°C bis +180°C / -60°C bis +180°C

RoHS

// langes Anschlussgewinde auf Anfrage  
// weitere Größen auf Anfrage

AG	GL mm	H mm	SW mm	Art.-Nr.	Art.-Nr.	Art.-Nr.
				NBR -20°C bis +95°C	FKM -20°C bis +180°C	VMQ (Silikon) -60°C bis +180°C
M12 x 1,5	6,5	9,5	14	1.152.1200.50	1.153.1200.50	1.154.1200.50
M16 x 1,5	6	9	19	1.152.1600.50	1.153.1600.50	1.154.1600.50
M20 x 1,5	6	9,5	22	1.152.2000.50	1.153.2000.50	1.154.2000.50
M25 x 1,5	7	10,5	30	1.152.2500.50	1.153.2500.50	1.154.2500.50
M32 x 1,5	8	12,5	41	1.152.3200.50	1.153.3200.50	1.154.3200.50
M40 x 1,5	8	13	46	1.152.4000.50	1.153.4000.50	1.154.4000.50
PG 7	5	8	14	1.152.0700.01	1.153.0700.01	1.154.0700.01
PG 9	6	9	17	1.152.0900.01	1.153.0900.01	1.154.0900.01
PG 11	6	9,5	20	1.152.1100.01	1.153.1100.01	1.154.1100.01
PG 13,5	6,5	10	22	1.152.1300.01	1.153.1300.01	1.154.1300.01
PG 16	6,5	10	24	1.152.1600.01	1.153.1600.01	1.154.1600.01
PG 21	7	10,5	30	1.152.2100.01	1.153.2100.01	1.154.2100.01
PG 29	8	12,5	41	1.152.2900.01	1.153.2900.01	1.154.2900.01
PG 36	8	13	50	1.152.3600.01	1.153.3600.01	1.154.3600.01

